



**Model: KSC-108COMBO-N**

1U Rackmount 8 ports CAT6 KVM Switch

**Rear view of KSC-108COMBO-N**



## Main Feature

- Combo CAT6 KVM with 8 / 16 /32 ports with 1U 19'' Rackmount design
- Support a Local USB console
- Support an optional remote console (Cat5 based or Over-IP)
- VGA-USB / VGA-PS2 connector dongle up to 40 meters (132 feet) Cat5/6 cable
- Cascade switches up to 8 levels and Mix switches between Cat5/6 & DB-15 KVM
- Mix PS/2,USB,SUN & MAC with Multi-Platform switch capability
- Auto scan for monitoring PCs ,easy select via push buttons, Hot keys, OSD Hot Pluggable, no software or drivers required
- Easy & quick installation

**Model: KSC-116COMBO-N**

1U Rackmount 16 ports CAT6 KVM Switch


**Rear view of KSC-116COMBO-N**



**Model: KSC-132COMBO-N**

1U Rackmount 32 ports CAT6 KVM Switch

**Rear view of KSC-132COMBO-N**



## Specification

Product Model	KSC-108COMBO-N	KSC-116COMBO-N	KSC-132COMBO-N
LEDs / Port	8	16	32
Power	1		
Computer Connections	8	16	32
Maximum Computer Connections	232	240	256
Computer Connectors	RJ-45 Connector		
Console Ports	1 ( One Local, up to 1920x1440 resolution ), plus 1 Optional Modules : Selectable CAT5/6-Based or IP Remote Console		
CAT5-Based Remote Console (Optional)	1 x RJ-45 connector up to 300 Meters ( 1000 feet ) with CAT5/6 cable; Remote receiver support 1 x VGA ( up to 1280x1024 resolution ), 2 x USB for KB & Mouse , 1 x KVM port for connecting an extra PC		
IP-Based Remote Console Module (Optional)	1 x RJ-45 connector for 10/100M Ethernet ( remote console up to 1600x1200 resolution ), 1 x DB-9 male connector for Modem ,Null Modem and serial power control , 1 x mini USB 2.0 receptacle		

Daisy Chaining	Daisy Chainable up to 8 levels ; Connector : DB-15 ( female type)	
Computer Selection	On Screen Display ( OSD ) , Hot Key , Push Button	
Hotkey	Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)	
Auto-Scan Intervals	5 - 99 Sec.	
Keyboard / mouse Emulation	PS/2	
Video Resolution (Remote Console)	1600 x 1200 for CAT5-Based 500 feet remote console; 1024 x 768 for CAT5-Based 1000 feet remote console; 1600 x 1200 for IP-Based remote console	
Power Adapter	AC 100-240V , 50/60Hz External Adapter	
Housing	Metal	
Size	19" Rack mount, 1U	
Environment	Operating Temperature	0 to 50°C
	Store Temperature	-20 to 60°C
	Humidity	10% to 90%, non-condensing
Net / Gross Weight ( KG )	3kg / 4kg	
Dimensions ( W x H x D )	448 x 44 x 167 mm	
Certificated	CE/FCC	
<b>Ordering Information</b>		
KSC-108COMBO-N	1U Rackmount 8 ports CAT6 KVM Switch	
KSC-116COMBO-N	1U Rackmount 16 ports CAT6 KVM Switch	
KSC-132COMBO-N	1U Rackmount 32 ports CAT6 KVM Switch	
KUD	USB CAT5 KVM Dongle	
KPD	PS2 CAT5 KVM Dongle	