


Model: EIPC-J1900-12 (without Touch screen) EIPC-J1900-12T (with Touch screen)

**12.1" Marine Suitable Intel Celeron J1900 Panel PC - 4 x COM; IP65 front protection; Optional - Touch Screen & WIFI**




## Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 12.1" XGA LED Panel support 1024x768 pixels
- Intel Celeron J1900 ( 2.0GHz, Quad Core, 2MB Cache) Processor
- Rugged construction design
- Front 6mm Aluminum bezel - NEMA4 / IP 65 compliant
- 4 x COM (3 x RS232 and 1 x RS422/485)
- (Optional - Touch Screen) Front hardness glass protect screen
- (Optional - WIFI) MINI PCI-E WIFI Module with Antenna
- Panel (Flush) mounting with clip
- Meet standard VESA hole ( 75 & 100 mm ), support desk top stand / wall mount / swing arm mounting

Specification	
Product Model	EIPC-J1900-12 / EIPC-J1900-12T
CPU	Intel Celeron J1900 ( 2.0GHz, Quad Core, 2MB Cache, up to 2.41 GHz w/ burst frequency enabled)
Chipset	Intel® SOC integrated
Memory	1 x DDR3L SO-DIMM Socket up to 8GB
Storage	Space for 1 x 2.5" Drive Bay
Display	Display Type : 12.1" XGA <u>LED Panel</u> LCD Resolution : 1024 × 768 Luminance : 500 cd/m2 View Angel : 160° (H) , 160° (V)
Audio	Realtek ® ALC662, 5.1 channel surround audio
LAN	2 x Realtek ® RL8111x (Gigabit ) 10/100/1000Ethernet

USB port	4 x USB 2.0
VGA port	Intel HD Display output
Expansive interface	1 x Mini PCI-E
Back panel I/O port	2 x PS2 for KB/Mouse; 2 x RJ45; 4 x USB 2.0; 1 x VGA ; 1 x Lin-in / Lin-out; 1 x LPT; 4 x COM; 1 x HDD/PWR LED; 1 x Power / Reset Switch; 1 x PWR-In 3 PIN Terminal Block
Supporting OS	DOS; Windows 7/8.1/10; Linux
Touch Screen ( optional )	Internal USB interface controller - Resistive Touch Type: Analog resistive type : 25VDC $\geq$ 20M $\Omega$ Resolution: continuous Light transmission: 80% or more Power consumption:<5V @1mA Surface hardness : 3H Operating force : $\leq$ 100g Life expectancy : 35 Million
Wireless LAN ( optional )	MINI PCI-E WIFI Module with Antenna
Power Supply	12VDC input with 3 pin termination block
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: -5°C to 60°C Relative humidity: 10% to 90%non-condensing Vibration: 17 to 500HZ 1G PTP; Shock: 1G /peak( 11m sec)
Compliance	CE; FCC; ROHS
Dimension W x H x D	322 x 247 x 70 mm
<b>Ordering Information:</b>	
EIPC-J1900-12	12.1" Marine Suitable Panel PC - Intel Celeron J1900, with 100-240VAC to 12VDC adapter
EIPC-J1900-12T	12.1" Marine Suitable Panel PC - Intel Celeron J1900, with Touch Screen, with 100-240VAC to 12VDC adapter
<u>Optional</u> - RAM	4 to 8GB DDR3L SO-DIMM RAM
<u>Optional</u> - SSD / HDD	32 GB to 1TB SSD / 500GB to 1TB 2.5" SATA HDD
<u>Optional</u> - WIFI	MINI PCI-E WIFI Module with Antenna
<u>Optional</u> - OS	Windows 7/8.1/10 Professional

## Structure Diagram



CUT OUT DIMENSION(309.5x237mm) UNIT:mm