

Model: IDPMB-27W-BNC
27" Industrial Panel Monitor (Wide Screen)



Main Feature

- 27" Full HD LED Panel support 1920 × 1080 pixels
- 6mm Aluminum front bezel with strengthen glass
- Rugged construction design
- Input signal : VGA + HDMI +BNC + Audio
- Build in 2 x 8 Watts stereo speaker
- OSD control keys to optimize the display
- IP65 compliant front panel
- AC 100-240V wide range external AC adapter
- Panel mounting with clip, and wall mount bracket included
- Meet standard VESA hole (100x100 mm)


Specification	
Product Model	IDPMB-27W-BNC
LCD Panel	Display Type : 27" Full HD LED Panel Resolution : 1920 x 1080 Max. color : 16.7M Luminance : 300 cd/m2 View Angel : 178° (H), 178° (V) Pixel Pitch : 0.311 x 0.311 mm Contrast Ratio : 3000 : 1 Response Time : 25 ms Power Consumption : 45 Watt LCD MTBF : 50,000hrs
Signal Input	VGA (15 pin D-sub connector) + HDMI + BNC + audio input (audio jack)
Protect Glass	3 mm strengthen glass
Speaker	Built-in 2x stereo speakers(8 watt)

OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, PIP, Auto tune and recall
Power Supply	Input: 100-240VAC,50/60Hz Output: DC12V@ 5A /60W ,external ac adapter
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: 0 °C to 50 °C Storage temperature: -20 °C to 60 °C Storage humidity: 10% to 95%, non-condensing Vibration: 17 to 500HZ 1G PTP Shock: 1G /peak(11m sec)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 605 x 380 x 47 mm

Ordering Information

IDPMB-27W-BNC	27" Industrial Panel Monitor (Wide Screen)
---------------	--

Structure Diagram Unit: mm



CUT OUT DIMENSION (658x403mm) UNIT:mm