

Model: IPC-4410

4U Server Case with 10 x Hot-Swappable SAS/SATA Drive Bay, SATA backplane



Specification

- Form Factor: 4U, 19" Rackmount Chassis
- Color: Silver and Black
- Motherboard Support: MINI-ITX (6.7''x6.7''), Mirco ATX (9.6''x9.6''), ATX (12"x9.6''), CEB (12"x10.5''), EEB (12"x13'')
- Processor Support: Supports dual, single Intel® / AMD processors
- Power Supply Support: standard ATX, PS2 / Mini Redundant
- Dimensions (H x W x D): 178mm x 480mm x 690mm
- Expansion Slots: 7
- Drive Bay: 10 x 2.5'' / 3.5'' hot-swappable SAS/SATA trays, 4 x 2.5'' and 1 x 3.5'' (or 3 x 5.25'') bay
- Backplane: 10 x SAS/SATA connectors
- Front Panel: Power ON/OFF switch, System Reset switch, 1 x USB 2.0 and 1 x USB 3.0 port
- Front LED: 1 x Power ON, 1 x HDD activity, 3 x LAN activity, 1 x Alarm
- System Cooling: 3 x 120mm middle fans (Hot-swap type, Molex connector), 2 x 80mm rear fans
- Material: 1 - 1.2mm steel
- Operating Temperature: 0/50 °C
- Storage Temperature: -20/60 °C
- Storage Humidity: 10% to 90%, non-condensing
- Packing: 250mm x 560mm x 830mm (H x W x D)
- Weight: 15 Kg(net), 18 Kg (gross)

Optional items

- Sliding Rail (For server rack depth 800 to 1000mm)
- Telescopic Sliding Rails For server rack depth 800 to 1200mm
- MINI-SAS to 4 x SATA Breakout cable (to support with SAS controller)