

Model: KH-202

2 Port USB Dual Display HDMI / Audio KVM Switch, with 2 x 1.8 meter KVM Cables - USB & HDMI interface



Primary Display - HDMI Line - Scondary Display - HDMI Line

Main Feature

- 2 Port HDMI USB2.0 KVM Switch
- One dual-screen USB console controls two HDMI interface computers and one additional USB devices
- One front port USB hub 2.0 built in, fully compliant USB 2.0 specification
- Superior video quality supports 480i, 480p, 720p, 1080i, 1080p, and 4K (resolution: 3,840x2,160 @ 30Hz)
- Independent switching of KVM, USB peripheral, and audio focus via front panel push buttons and hotkeys
- HDMI digital monitor support fully compliant with HDMI; also HDCP compliant
- Dolby True HD and DTS HD Master Audio support
- Multiplatform support Windows, Linux, and Mac
- BIOS hardware connection, no need driver program and controlling software
- Auto scan Mode for monitoring all computers and HDMI devices

Company Registration No.: 200901437Z

Website: www.sg-norco.com



Specification		
Product Model		KH-202
Computer Connections		2
Port Selection		Front push button or Hot-key
Front LED Indicator		2 x On-line (Red), 2 x Selected (Green)
Connectors		
Console Ports		2 x USB Type A Female (rear panel) 1 x HDMI Female (Black)
KVM Port		2 x USB Type B Female 2 x HDMI Female (Black) 2 x 3.5 mm Audio Jack Female
USB Hub		1 x Front USB Type A Female
Power		1 x DC Jack
Video Resolution		480i, 480p, 720p, 1080i,1080p, and 4K (3,840x2,160 @ 30Hz)
Scan Interval		1-99 seconds (default: 5 sec.)
Power Consumption		5 VDC / 5 Watt
Environment	Operating Temperature	0 to 50°C
	Store Temperature	-20 to 60°C
	Humidity	10% to 90%, non-condensing
Net / Gross Weight (KG)		0.6 Kg
Dimensions (WxHxD)		132 x 92 x 66 mm
Ordering Information		
KH-202		2 Port USB Dual Display HDMI / Audio KVM Switch, with 2 x 1.8 meter KVM Cables - USB & HDMI interface