

Model: KHDMI-1916W

1U Rackmount 18.5" LCD with 16 port HDMI KVM switch, 16 x 1.8 meter KVM Cable



16 x 1.8 meter KVM Cable

Main Feature

- Build-in 16 ports HDMI KVM switch controls sixteen directly connected computers
- A-Grade 18.5'' LED-backlit LCD panel with maximum resolution of 1920 x 1080
- LCD module rotates up to 120 degrees for a more comfortable viewing angle
- Rear 2 x USB ports for additional Keyboard and Mouse connection
- Supporting DOS, Windows, Netware, Unix, Linux, Mac OS
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- 1U 19'' rack mountable design, metal case - Integrated full size keyboard and touchpad
- Easy for operate, allow smoothly pulling with self-locking at end position
- Customized Keyboard Language support upon request

| Specification | | |
|---------------|----------------|--|
| Product Model | | KHDMI-1916W |
| LCD | Size | A-Grade 18.5'' LED-backlit LCD panel (Ratio: 16:9) |
| | Resolution | 1920 x 1080 @ 60Hz |
| | Max. color | 16.7M |
| | Luminance | 250 cd/m2 |
| | View Angel | 170° (H), 160° (V) |
| | Pixel Pitch | 0.213 x 0.213 mm |
| | Contrast Ratio | 1000 : 1 |
| | LCD MTBF | 50,000 hours |

| | | |
|---|-----------------------|---|
| Computer Connections | Direct / Maximum | 16 |
| Computer Port Selection | | OSD, Hot Key, Push Button |
| Connector | Power | 12 VDC Input |
| | Computer | 16 x HDMI Female port |
| | USB port | 16 x USB-B Type, and for additional Keyboard & Mouse (1@Front & 2@Rear) |
| LEDs | Port | 16 |
| | Power | 1 |
| Button / Switch | Power Switch | Button |
| | LCD Adjustment | Button |
| Hotkey | | Provide various Hotkey (Scroll/Shift/ Alt/ Ctrl + Num) |
| Auto-Scan Intervals | | 3 - 60 Seconds |
| Power Rating (AC to 12VDC/4A adapter) | | 100-240VAC, 50/60Hz |
| Environment | Operating Temperature | -10 - 50°C |
| | Store Temperature | -20 - 60°C |
| | Humidity | 0-80% RH, NC |
| Housing | | Heavy Duty Steel |
| Size | | 1U, 19" Rackmount |
| Rack Installation Depth (front rails to rear rails) | | 556 - 900mm (Minimum to Maximum adjustable) |
| Net / Gross Weight | | 17KG / 19KG |
| Dimensions (W*D*H) | | 443 x 556 x 45 mm |
| Certificated | | CE/FCC |
| Order Information | | |
| KHDMI-1916W | | 1U Rackmount 18.5" LCD with 16 port HDMI KVM switch, 16 x 1.8 meter KVM Cable |

Structure Diagram Unit :mm

