

**Model:** KVM-15xxCOMBO-S (KVM-1501COMBO-S,KVM-1508COMBO-S,KVM-1516COMBO-S)  
1U Rackmount 15" TFT LCD KVM (Short Depth - 406mm)



## Main Feature

- 1 PS/2 console controls 1/8/16 directly connected computers
- 86 keys keyboard with touch pad
- Cascade switches up to 8 levels and Mix switches between Cat5 & DB-15 KVM
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports

Specification				
Product Model		KVM-1501COMBO-S	KVM-1508COMBO-S	KVM-1516COMBO-S
LCD	Size	15" TFT		
	Resolution	1024 x 768		
	Max.color	16.7 M		
	Luminance	300 cd/m2		
	View Angle	178° (H) , 178° (V)		
LEDs / Port		1	8	16
Power		1		
Computer Connections		1	8	16
Maximum Computer Connections		225	232	240
Computer Connectors		2 x PS2, 1 x USB, 1 x VGA / 8 x DB -15 female / 16 x DB -15 female		
Daisy Chaining		Daisy Chainable up to 8 levels ; Connector : DB-15 ( female type)		
Computer Selection		On Screen Display ( OSD ) , Hot Key , Push Button		

Hotkey	Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)	
Auto-Scan Intervals	5 - 99 Sec.	
Keyboard / mouse Emulation	PS/2	
Power Adapter	AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt	
Housing	Metal	
Size	19" Rack mount, 1U	
Environment	Operating Temperature	0 - 50°C
	Store Temperature	-20 -60°C
	Humidity	10% to 90%,non-condensing
Physical Dimensions ( W x H x D )	482.6 x 43.6 x 406.4 mm	
Certificated	CE/FCC	
<b>Ordering Information</b>		
KVM-1501COMBO-S	1U Rackmount 15" TFT LCD ,with 1 port KVM switch (Short Depth)	
KVM-1508COMBO-S	1U Rackmount 15" TFT LCD, with 8 port KVM switch (Short Depth)	
KVM-1516COMBO-S	1U Rackmount 15" TFT LCD, with 16 port KVM switch (Short Depth)	
KCVU-018 (optional)	USB, 2 in 1 KVM Cable , 1.8 meter length	
KCVU-030 (optional)	USB, 2 in 1 KVM Cable , 3.0 meter length	
KCVU-050 (optional)	USB, 2 in 1 KVM Cable , 5.0 meter length	
KCVP-018 (optional)	PS/2, 3 in 1 KVM Cable , 1.8 meter length	
KCVP-030 (optional)	PS/2, 3 in 1 KVM Cable , 3.0 meter length	
KCVP-050 (optional)	PS/2, 3 in 1 KVM Cable , 5.0 meter length	

**Structure Diagram**

Unit :mm

