

**Model: KVM-1708COMBO-S-IP**  
**1U Rackmount 17" TFT LCD ,with 8 port KVM switch (Short Depth), IP65**



## Main Feature

- IP65 front protection for LCD screen
- IP68 - 98 keys Silicon keyboard with touch pad
- Short depth (460mm) 19'' 1U Rackmount Design
- 1 x USB / PS2 console controls 1/8/16 directly connected computers
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)

Specification		
Product Model		KVM-1708COMBO-S-IP
LCD	Size	17" TFT
	Resolution	1280 x 1024
	Backlight	LED
	Luminance	250 cd/m2
	View Angle	176° (H) , 170° (V)
	Maximum Color	16.7M
	Contrast Ratio	1000 : 1
LEDs / Port		8
Power LED		1
Computer Connections		8
Maximum Computer Connections		232
Computer Connectors		8 x DB-15 female
Daisy Chaining		Daisy Chainable up to 8 levels; Connector: DB-15 (female type)

Computer Selection		On Screen Display ( OSD ) , Hot Key , Push Button
Hotkey		Provide various Hotkey ( Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)
Auto-Scan Intervals		5 - 99 Sec.
Keyboard / mouse Emulation		PS/2
Power Adapter		AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt
Housing		Metal
Size		19" Rack mount, 1U
Environment	Operating Temperature	0-50°C
	Store Temperature	-20-60°C
	Humidity	10% to 95%, non-condensing
Physical Dimensions ( W x H x D )		443 x 42 x 457.2 mm
Packing Dimensions ( W x H x D )		605 x 168 x 700 mm
Certificated		CE/FCC
<b>Ordering Information</b>		
KVM-1708COMBO-S-IP (1U Rackmount 17" TFT LCD, with 8 port KVM switch (Short Depth), IP65)		
KCVU-018 (USB, 2 in 1 KVM Cable , 1.8 meter length)		KCVP-018 (PS/2, 3 in 1 KVM Cable , 1.8 meter length)
KCVU-030 (USB, 2 in 1 KVM Cable , 3.0 meter length)		KCVP-030 (PS/2, 3 in 1 KVM Cable , 3.0 meter length)
KCVU-050 (USB, 2 in 1 KVM Cable , 5.0 meter length)		KCVP-050 (PS/2, 3 in 1 KVM Cable , 5.0 meter length)

**Structure Diagram** Unit :mm

