

Model: KVM-1701W-COMBO-S (1U Rackmount 17.3" Full HD LCD with 1 port KVM switch - Short Depth)
KVM-1708W-COMBO-S (1U Rackmount 17.3" Full HD LCD with 8 port KVM switch - Short Depth)
KVM-1716W-COMBO-S (1U Rackmount 17.3" Full HD LCD with 16 port KVM switch - Short Depth)



Main Feature

- 1 PS/2 console controls 1/8/16 directly connected computers
- 88 keys keyboard with touch pad
- Cascade switches up to 8 levels and Mix switches between Cat5 & DB-15 KVM
- Support DOS, Windows, Netware, Unix, Linux, Mac OS
- Hot Pluggable - Add or remove connected PCs without having to power down the KVM switch/PCs
- No software required - easy PC selection via Push Buttons, Hot Keys or OSD (on screen display)
- Auto Scan Mode for monitoring PCs
- Firmware upgradeable for staying compatible with new coming computers
- Metal case, rack mountable Support DDC2B for all ports

Specification				
Product Model		KVM-1701W-COMBO-S	KVM-1708W-COMBO-S	KVM-1716W-COMBO-S
LCD	Size	17.3" Full LED Panel		
	Resolution	1920 X 1080		
	Max. color	26.2M		
	Luminance	300 cd/m2		
	View Angel	140° (H) , 120° (V)		
	Pixel Pitch	0.1989 x 0.1989 mm		
	Contrast Ratio	500 : 1		
LEDs / Port	1	8	16	
Power	1			
Computer Connections	1	8	16	
Maximum Computer Connections	225	232	240	
Computer Connectors	2 x PS2, 1 x USB, 1 x VGA / 8 x DB -15 female / 16 x DB -15 female			
Daisy Chaining	Daisy Chainable up to 8 levels ; Connector : DB-15 (female type)			
Computer Selection	On Screen Display (OSD) , Hot Key , Push Button			
Hotkey	Provide various Hotkey (Scroll-Lock/ Cap-Lock / Num-Lock / Alt-Ctrl-Win)			
Auto-Scan Intervals	5 ~ 99 Sec.			
Keyboard / mouse Emulation	PS/2			
Power Adapter	AC 100-240V , 50/60Hz , DC 12V / 4A , 48Watt			
Housing	Metal			
Size	19" Rack mount, 1U			
Environment	Operating Temperature	0-50°C		
	Store Temperature	-20-60°C		
	Humidity	10% to 90%,non-condensing		
Net / Gross Weight	14kg / 17kg			
Physical Dimensions (W x H x D)	483 x 42 x 457 mm			
Packing Dimensions (W x H x D)	605 x 168 x 700 mm			
Certificated	CE/FCC			
Ordering Information				
KVM-1701W-COMBO-S	1U Rackmount 17.3" Full HD LCD, with 1 port KVM switch (Short Depth)			
KVM-1708W-COMBO-S	1U Rackmount 17.3" Full HD LCD, with 8 port KVM switch (Short Depth)			
KVM-1716W-COMBO-S	1U Rackmount 17.3" Full HD LCD, with 16 port KVM switch (Short Depth)			
KCVU-018	USB, 2 in 1 KVM Cable , 1.8 meter length			
KCVU-030	USB, 2 in 1 KVM Cable , 3.0 meter length			
KCVU-050	USB, 2 in 1 KVM Cable , 5.0 meter length			
KCVP-018	PS/2, 3 in 1 KVM Cable , 1.8 meter length			
KCVP-030	PS/2, 3 in 1 KVM Cable , 3.0 meter length			
KCVP-050	PS/2. 3 in 1 KVM Cable , 5.0 meter length			

Structure Diagram Unit : mm

