

Model: KVM-1901COMBO-DR
1U Rackmount Dual Rail 19" 1 port LCD KVM
with KVM cable - PS/2 & USB Interface



Main Feature

- LCD Monitor & Keyboard could pull-out & push back independently
- Support combo interface for PS/2 & USB
- Controls one set of PC or KVM-Switch
- OSD (on screen display) function for LCD display
- No software & driver required - Hot pluggable
- Built-in AUTO self-locking & releasing mechanism system at end position (safety feature)
- Metal case, rack mountable - Integrated 19" LCD Panel with 104 keys keyboard and touchpad

Specification		
Product Model		KVM-1901COMBO-DR
LCD	Size	19" TFT
	Resolution	1280 X 1024
	Max. color	16.7M

	Luminance	300 cd/m2
Computer Connections	Power	AC Inlet
	VGA DB-15(Female)	1
	Keyboard MD-6 (Female)	1
	Mouse MD-6 (Female)	1
	USB(A type)	1
Button / Switch	Power Switch	Rock Switch
	LCD Adjustment	Button
Auto-Scan Intervals		5 - 99 Sec.
Keyboard / mouse Emulation		PS/2
Power Input Rating		100-240VAC ; 50/60Hz ; 1A
Power Consumption		37W
Environment	Operating Temperature	0-50°C
	Store Temperature	-20-60°C
	Humidity	0-80% RH , NC
Housing		Heavy Duty Steel
Size		1U 19" Rack mount
Net / Gross Weight		23 / 27 kg
Dimensions (W*D*H)		482 x 700 x 44 mm
Certificated		CE/FCC
Order Information		
KVM-1901COMBO-DR		1U Rackmount Dual Rail 19" 1 port LCD KVM, with KVM cable - PS/2 & USB Interface

Structure Diagram

Unit :mm

