

Model: KVM-2401HD-4K

1U Rackmount 24" 1 port 4K LCD KVM, with 1.8 meters KVM cable - HDMI, DP & USB Interface



Front USB Port



Rear I/O for KVM-2401HD-4K

Features

- 1U Rackmount 23.8" widescreen LCD Console Drawer
- Pivot Screen with HDMI & Display Port
- Maximum resolution 3840 x 2160
- Supporting resolution 1920 x 1200 and 1920 x 1080...
- Front 1 x USB and Rear 2 x USB with USB 2.0 Hub
- Integrated with 104-key keyboard with Touch-pad
- Built-in AUTO self-locking mechanism system
- Build-in 2x 2 watts speakers

Specification		
Product Model		KVM-2401HD-4K
LCD	Size	23.8"
	Resolution	3840 X 2160
	Max. color	1.0737 Billion
	Luminance	300 cd/m2
Computer Connections	Power	AC Inlet
	HDMI 2.0	1
	Display Port 1.4	1
	USB (for Keyboard & Mouse)	1
	USB 2.0 Hub	1 @ front and 2 @ Rear

Button / Switch	Power Switch	Rock Switch
	LCD Adjustment (OSD)	Button
Auto-Scan Intervals		5 - 99 Sec.
Power Input Rating		100-240VAC ; 50/60Hz
Power Consumption		48W
Environment	Operating Temperature	0 - 50°C
	Store Temperature	-20 - 60°C
	Humidity	0-80% RH , NC
Housing		Heavy Duty Steel
Size		1U, 19" Rack mount
Net / Gross Weight		20 / 26 kg
Dimensions (W*D*H)		448 x 699 x 44 mm
Packing Dimensions (W*D*H)		720 x 830 x 170 mm
Order Information		
KVM-2401HD-4K		1U Rackmount 24" 1 port 4K LCD KVM, with 1.8 meters KVM cable - HDMI, DP & USB Interface

Structure Diagram Unit :mm

