

**Model: PWS-700-17W**  
**Rugged Portable 17.3" Full HD Workstation**



**Main Feature**

- Rugged Portable Workstation
- 17.3" Full HD LED Panel support 1920 × 1080 pixels
- Aluminum alloy chassis
- Front panel Built in OSD, integrated full function keypad and Touch pad
- Front Accessible USB 2.0 x 2, 3.5" HDD bay x 3
- With 1U 600 watt PSU
- Support Micro ATX & MINI-ITX Main Board

Specification	
<b>Product Model</b>	<b>PWS-700-17W</b>
<b>Main Board support</b>	Micro ATX (9.6" x 9.6"), Mini-ITX (6.7" x 6.7")
<b>Storage</b>	Space for 3 x 3.5" HDD drive bay
<b>Display</b>	Display Type : 17.3" Full HD LED Panel Resolution : 1920 x 1080 Luminance : 300 cd/m2 View Angel : 130° (H), 120° (V) Pixel Pitch : 0.1989 x 0.989 mm Contrast Ratio : 500 : 1 Response Time : 2 ms Power Consumption : 12W LCD MTBF : 50,000hrs
<b>Front OSD</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall
<b>Front Panel</b>	Power ON/OFF switch, 2 x USB 2.0, 1 x LAN
<b>Front LED</b>	1 x Power ON, 1 x HDD activity

DVI / VGA interface	Internal AD Board to convert
Speaker	2 x 2W internal stereo speaker
Expansive Slots	4 x Maximum
Power Supply	Input: 110-240VAC, 50/60Hz Output: 600W
Construction	Heavy duty steel and aluminum alloy
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45 °C) Storage temperature: -4 °F~140 °F (-20 °C to 60 °C) Storage humidity: 10% to 90%non-condensing Vibration: 17 to 500HZ 1G PTP Shock: 1G /peak( 11m sec)
Dimension W x H x D ( mm )	429 x 334 x 216 mm
<b>Ordering Information</b>	
PWS-700-17W	Rugged Portable 17.3" Full HD Workstation

**Structure Diagram** Unit :mm

