

**Model: R2A-600D1V2 (High Efficiency; Low Noise; 600watt + 600watt)  
600W Redundant Power Supply for 2U/3U chassis**



### Features

- Meet the RoHS COMPLIANT 2002/95/EC.
- Meet the WEEE Directive (2002/96/EC)
- Temperature Range: Operating 0°C ~ 40°C, Storage -20°C ~ 70°C
- Hold up time: 16 ms Minimum at full load & Normal input voltage.
- OVER POWER PROTECTION: 110~150%
- OVER VOLTAGE PROTECTION
- OVER CURRENT PROTECTION
- SHORT CIRCUIT PROTECTION
- Remote On/Off Control.
- Power Good Signal: On Delay 100ms to 500ms, off delay 1ms.
- Safety: To meet UL, TUV, CB, CE, FCC, BSMI, CCC.
- EMI noise Filter: FCC Class B, CISPR22 Class B
- Dimension (L x W x H): 265 X 101 X 84 mm / 10.43 x 3.98 x 3.3 (inches)

### AC Input

- Input voltage: 90 ~ 264VAC Full-Range.
- Frequency: 47 - 63 Hz.
- Input Current: 10A for 115VAC, 5A for 230VAC.
- Inrush Current: 25A for 115VAC, 50A for 230VAC.
- The Minimum efficiency of the power supply is 80% at full load and 1150Vac/60HZ input.
- The minimum power factor at full load shall be 0.98 / 115V 60 Hz and 0.96 / 230V 50 Hz.

