

Model: RMM-5X3-SDI
 2U, Triple 5" TFT LCD Rack Mount Monitor with SDI Input and Output



Main Feature

- 2U, 19" Rack Mount triple 5" TFT LCD Monitor
- Full 1080p HD resolution (1920 x 1080)
- Inputs: HDMI, 3G-SDI, LAN and Tally
- Output: HDMI, 3G-SDI
- HDMI supports 4K @ 60 Hz (2160p), 3G-SDI supports 1080p and lower
- Monitor and Control via LAN (IP address)
- Front-access OSD Controls

Specification	
Product Model	RMM-5X3-SDI
LCD Panel	Display Type : 5" Full HD LED Panel LCD Resolution : 1920 x 1080 Luminance : 450 nit Contrast: 1,000:1 View Angel : 160°(H), 160°(V)
Signal Input	HDMI x3 + 3G-SDI x3 + LAN + Tally
Signal Output	HDMI x3 + 3G-SDI x3 + Audio (Ear Plug)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Power Supply	DC12V@ 2.5A /30W, External AC adapter (12-24VDC Wide range input)
Construction	Heavy duty steel

Environment	Operating temperature: 32 °F-113 °F (0 °C to 45 °C) Storage temperature: -4 °F-140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40°C , on-condensing Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 480x116x88mm Packing Dimension: 600x190x 140mm
Weight	NET weight: 2.5KG Gross weight: 4KG
Ordering Information	
RMM-5X3-SDI	2U, Triple 5" TFT LCD Rack Mount Monitor with SDI Input and Output

Structure Diagram Unit :mm

