

Model: RMM-6X2
3.5U, 19" Rack Mount Dual 6.4" TFT LCD Monitor



Specification	
Product Model	RMM-6X2
LCD Panel	Display Type : 6.4" VGA TFT LCD Resolution : 640x480 Max. color : 262K Luminance : 400 cd/m2 View Angel (L/R ,U/D): 50/50, 15/35 Pixel Pitch : 0.2025 x 0.203 mm Contrast Ratio : 400 : 1 Response Time : 40 ms Power Consumption : 4.8W LCD MTBF : 20,000hrs
Signal Input	VGA , Video, S-Video
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
Power Supply	DC12V@ 4A /48W ,external ac adapter
Construction	Heavy duty steel
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45 °C) Storage temperature: -4 °F~140 °F (-20 °C to 60 °C) Storage humidity: 10% to 95%@ 40°C , on-condensing Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs
Dimension W x H x D (mm)	Dimensions: 482.6*153.6*62.6 mm Packing Dimension: 600x190x 320mm
Weight	NET weight: 5.4KG Gross weight: 6.5KG

Structure Diagram Unit :mm

