

Model: RPC-2208  
2U Server Case with 8 Hot-Swappable SATA Drive Bay, Mini SAS  
Backplane



## Specification

- Form Factor: 2U, 19" Rackmount Chassis
- Color: Black
- Motherboard Support: ATX (12"x9.6"), CEB (12"x10.5"), EEB (12"x13")
- Processor Support: Supports dual, single Intel® / AMD processors
- Power Supply Support: standard 2U ATX, 1+1 Redundant
- Dimensions ( W x D x H ): 16.9" x 25.5" x 3.5 " (430mm x 650mm x 88mm)
- Expansion Slots: 7

- Drive Bay: 8 x 3.5" or 2.5" hot-swappable SATA trays, 1 x slim DVD-ROM bay, 2 x 2.5" drive bay
- Backplane: 2 x SFF-8087 Mini SAS connectors
- Front Panel: Power ON/OFF switch, System Reset switch, 2 x USB 2.0 port
- Front LED: 1 x Power ON, 1 x HDD activity, 2x LAN activity
- System Cooling: 5 x 80mm middle fans (10,000RPM)
- Operating Temperature: 0/50 °C
- Storage Temperature: -20/60 °C
- Storage Humidity: 10% to 90%, non-condensing
- Packing: Double Carton boxes, 570mm x 830mm x 210mm
- Weight: 10.7 Kg(net), 13.5 Kg (gross)

## Optional items

- Sliding Rail