

Model: RPC-4220
4U Server Case with 20 Hot-Swappable SATA Drive Bay, Mini-SAS
Backplane



Specification

- Form Factor: 4U, 19" Rackmount Chassis
- Color: Black
- Motherboard Support: ATX (12"x9.6"), CEB (12"x10.5"), EEB (12"x13")
- Processor Support: Supports dual, single Intel® / AMD processors
- Power Supply Support: standard ATX, Mini Redundant
- Dimensions (W x D x H): 16.9" x 25.5" x 7.0 " (430mm x 650mm x 176mm)
- Expansion Slots: 7
- Drive Bay: 20 x 3.5" or 2.5" hot-swappable SATA trays, 1 x slim DVD-ROM bay, 2 x 3.5" drive bay

- Backplane: 5 x SFF-8087 Mini SAS connectors
- Front Panel: Power ON/OFF switch, System Reset switch, 1 x USB 2.0 port
- Front LED: 1 x Power ON, 1 x HDD activity, 2x LAN activity
- System Cooling: 4 x 80mm middle fans (10,000RPM), 2 x 80mm rear fans (3,000RPM)
- Operating Temperature: 0/50 °C
- Storage Temperature: -20/60 °C
- Storage Humidity: 10% to 90%, non-condensing
- Packing: Double Carton boxes, 570mm x 830mm x 310mm
- Weight: 17.5 Kg(net), 20.5 Kg (gross)

Optional items

- Sliding Rail