

Model: SSPM-22APCT-HB
21.5" High Brightness Industrial Stainless Steel Panel Monitor with PCT Touch



Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- 21.5" Full HD LED panel support 1920x1080 pixels
- Front 5.5mm Stainless Steel bezel with NEMA4 / IP 65 compliance
- Front flat glass (6H Hardness) with projected capacitive Multi Touch Screen
- Supports 10 points multi-touch via USB interface in Windows 7/8.1/10...
- Slim design for Panel mount / Wall mount easy installation
- Input signal : VGA + DVI-D + HDMI + Audio + USB
- Meet standard VESA hole (75x75 & 100X100mm), support desktop stand/wall mount /swing arm mounting

Application:

Kiosk; Digital Signage; Factory Automation; Processor Automation; Marine / Offshore Industrial ...

| Specification | |
|---------------|---|
| Product Model | SSPM-22APCT-HB |
| LCD Panel | Display Type : 21.5" Full HD <u>LED Panel</u> Resolution : 1920x1080 Max. color : 16.7M Luminance : 700 cd/m ² View Angel : 170°(H), 160°(V) Contrast Ratio : 1000 : 1 LED backlight lifecycle : 50,000hrs |

| | |
|----------------------------|--|
| Signal Input | VGA + DVI-D + HDMI + Audio + USB |
| OSD | Auto; Menu; Left; Right; Exit/Select; Power On/Off |
| Touch Screen | Internal USB interface controller - Projected Capacitive Multi Touch (10 points) Light transmission: 85% or more Surface hardness : 6H Operation system : DOS; Windows XP / 7 / 8.1 / 10; Linux |
| Power Supply | Input: 100~240VAC, 50/60Hz Output: DC12V@ 5A /60W, external AC power adapter |
| Construction | Stainless Steel front panel with heavy-duty steel chassis |
| Environment | Operating temperature: -0 °C to 60 °C Storage temperature: -20 °C to 70 °C Storage humidity: 10% to 95%, non-condensing Vibration: 50 to 500HZ 1G PTP Shock: 10G /peak(11m sec) |
| Safety | CE/FCC/Rohs |
| Dimension W x H x D (mm) | 585 x 360 x 50 mm |

Ordering Information

| | |
|----------------|---|
| SSPM-22APCT-HB | 21.5" High Brightness Industrial Stainless Steel Panel Monitor with PCT Touch |
|----------------|---|

Structure Diagram (Mounting Hole Size: 556 x 347 mm)

