

Model: **SSPM-22WT**
21.5" All Around IP66 Stainless Steel Touch Monitor



USB, HDMI & Power adapter and Cables included - 2 meters length each

Main Feature

- LED Panel - Higher Brightness; Longer Life Span; Better Viewing Angle; Less Power Consumption ...
- Rugged Fanless Stainless Steel Cooling design
- Anti-scratch touch surface
- All around IP66 with waterproof connectors
- Industrial 5 wire Resistive touch screen, optional for PCT Touch
- 1 x HDMI, 2 x USB 2.0, 1 x Power-In
- 12 to 24VDC wide range input

Application:

Factory Automation, Food Processing Factory, Medical Equipment, Marine / Offshore Industrial, Kiosk

| Specification | |
|---------------|--|
| Product Model | SSPM-22WT |
| Display | Display Type : 21.5" Full HD <u>LED Panel</u> LCD Resolution : 1920 x 1080 Luminance : 250 cd/m2 View Angel : 178° (H), 178° (V) |
| I/O port | 1 x HDMI; 1 x USB 2.0; 1 x 12-24VDC input |
| Touch Screen | Internal USB or RS-232 <u>industrial grade 5 wire Resistive Touch controller</u> Resolution: 4096 x 4096 Light transmission: 80% or more Surface hardness : 3H Operating force : ≤100g Life expectancy : 35 Million Operation system : Windows XP / 7 / 8.1 / 10 / CE, DOS , Linux |
| Power Supply | AC 100-240V wide range external AC adapter 12V/5A |
| Construction | All Around Stainless Steel |

| | |
|----------------------------|---|
| Environment | Operating temperature: -10°C to 60°C Relative humidity: 10% to 95%non-condensing Vibration: 17 to 500HZ 1G PTP; Shock: 1G /peak(11m sec) |
| Compliance | CE; FCC; ROHS |
| Dimension W x H x D (mm) | 540 x 332 x 59 mm |

Ordering Information

| | |
|-----------|---|
| SSPM-22WT | 21.5'' All Around IP66 Stainless Steel Touch Monitor, with 100~240VAC to DC 12V 60W power adapter |
|-----------|---|

Structure Diagram

