

Model: STM-24  
24" CCTV Security Monitor



### Main Feature

- 24" Full HD LED Panel support 1920 × 1200 pixels
- Heavy duty steel chassis
- Rugged construction design
- Input signal : VGA + DVI + HDMI + 5 x BNC + Audio
- Build in 2 x 5 Watts stereo speaker
- OSD control keys to optimize the display, with Infrared Remote Controller
- AC 100-240V wide range AC power input
- Meet standard VESA hole ( 100 x 100 mm ), support desktop stand/wall mount /swing arm mounting

Specification	
Model	STM-24
LCD Panel	Display Type: 24" Full HD LED Panel Resolution: 1920 x 1200 Max. color : 16.7M Luminance : 400 nit View Angel : 178° (H), 178° (V) Pixel Pitch : 0.27 x 0.27 mm Contrast Ratio : 1200 : 1 Response Time : 8 ms Power Consumption : 45W LED MTBF : 50,000hrs
Video System	PAL, NTSC 640 x 480p @ 60Hz 720 x 480p @ 60Hz 720 x 576p @ 50Hz 1,280 x 720p @ 50/60Hz 1,920 x 1,080i @ 50/60Hz 1,920 x 1,080p @ 50/60Hz
Filter Type	3D Combo filter

Signal Input	VGA + DVI + HDMI + 4 x BNC + YPbPr (BNC) + 2 x Audio (RCA)
Signal Output	2 x BNC loop-out (for video recording)
Speaker	Built-in 2 x stereo speakers (5 watt)
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto tune and recall
Power Supply	Input: 100~240VAC, 50/60Hz
Power Consumption	Maximum: 60 watt
Construction	Heavy duty steel chassis
Environment	Operating temperature: 0 °C to 50 °C humidity: 10% to 95%, non-condensing
Dimension W x H x D ( mm )	550 x 366 x 94
Net Weight	9.5 KG
Ordering Information	
STM-24	24" CCTV Security Monitor

Structure Diagram (unit: mm)

